

SPECIFICATION DATA



Super
T SERIES

STAINLESS STEEL BASIC SELF-PRIMING CENTRIFUGAL PUMP



Model: T8A65S-B

Various Patents Apply

PUMP SPECIFICATIONS

Size	8" (203 mm) ASA Flanged Suction x 8" (203 mm) NPT - Female Discharge
Impeller Type	Semi-Open, Two Vane
Solids-Handling Capability	3" (76,2 mm) Spherical Diameter
Seal Type	Mechanical, Oil-Lubricated, Double Floating, Self-Aligning
Radial Bearing	Open Double Row Ball
Thrust Bearing	Open Double Row Ball
Bearing and Seal Cavity Lubrication	SAE 30 Non-Detergent Oil
Maximum Operating Pressure	83 psi (572 kPa)*
Max Temp of Liquid Pumped	160°F (71°C).*

PUMP MATERIALS

Casing	Stainless Steel CD4MCuN
Impeller	Stainless Steel CD4MCuN
Impeller Shaft	Stainless Steel 17-4 PH
Seal: Stationary Face	Silicon Carbide
Rotating Face	Silicon Carbide
Elastomer	Fluorocarbon FKM, (Viton® or Equivalent)
Replaceable Wear Plate:	Stainless Steel CD4MCuN
Removable Adjustable Cover Plate	Stainless Steel CD4MCuN
Removable Inspection Cover Plate	Stainless Steel CD4MCuN – 20 lbs. (9,1 kg.)
Flap Valve	Fluorocarbon FKM, (Viton® or Equivalent) with Stainless Steel Reinforcing
Seal Plate	Stainless Steel CD4MCuN
Bearing Housing	Stainless Steel CD4MCuN
Suction Flange	Stainless Steel CD4MCuN
Discharge Flange	Stainless Steel 316
Gaskets	Fluorocarbon FKM, (Viton® or Equivalent) and PTFE
O-Rings	Fluorocarbon FKM, (Viton® or Equivalent)
Hardware	Stainless Steel 316

*Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.

Standard Equipment: Stainless Steel 316 Pressure Relief Valve, Bearing and Seal Cavity Oil Level Sight Gauges.

Optional Equipment: Automatic Air Release Valve, Metal Bellows Seal, 120V/240V Casing Heater, High Pump Temperature Shutdown Kit, Drain Kit, Gauge Kit.
Stainless Steel CD4MCuN Suction and Discharge Spool Flanges:
8" ASA (Specify Model T8A65S-B /F)
200 mm DIN 2527 – PN 16 (Specify Model T8A65S-B /FM).



Shown with Optional Suction and Discharge Spool Flanges (Available in ASA or DIN Standard Sizes).

Super T Series Features and Benefits

Easy To Service And Maintain - Pump is mounted above liquid being pumped with only the suction line down in liquid.

Dual Bearing Protection – An atmospheric barrier along with two lip seals provide additional protection of the pump bearings (not available on 2" models).

Inspection Cover – Patented, lightweight inspection cover for easy access to the impeller without removing the entire backcover plate or piping (2" – 8" models).

5 Year Super T Series Warranty

Up To 3" Diameter Spherical Solids Handling (4" – 10" models).

Removable Rotating Assembly – The entire rotating assembly can be removed without disturbing the pump volute or piping allowing the rotating assembly to be easily repaired or quickly replaced with a new ready to drop in assembly.

APPROXIMATE DIMENSIONS AND WEIGHTS

NET WEIGHT	1348 LBS. (611 KG.)*
SHIPPING WEIGHT	1410 LBS. (640 KG.)*
EXPORT CRATE	36.9 CU. FT. (1,04 CU. M.)

*Add 40 LBS. (18,1 KG.) w/each spool flange

- ★ 24.00/[609,6] RECOMMENDED FOR REMOVAL OF BACK COVER PLATE
- T8AS-B /F / T8CSC-B /F - 13.00/[330,2] REQUIRED FOR REMOVAL OF BACK COVER PLATE
- T8DS-B /F / T8ESC-B /F - 14.50/[368,3] REQUIRED FOR REMOVAL OF BACK COVER PLATE

